

INNOVATIONS®



Aura

Product Application:

Wallcovering

Composition:

Olefin Composite

Backing:

Osnaburg

Mural Dimensions:

H: 204" (518 cm) V: 131" (333 cm)

Panel Dimensions: This mural consists of 4 panels; H: 51" (130 cm) V: 131" (333 cm)

Fire Testing:

ASTM E84 – Class A / EN 13501-1 : Euroclass B

Weight:

20 oz/lineal yard (452 gsm)

Typical Roll Size:

30 yards (27 meters)

Durability:

High Traffic

Type:

Type II

Environmental Attributes:

Phthalate Free / Ultra-Low VOCs EQ 4.1 / CA 01350 Certified / Recycled Content by Weight (MR 4.1/4.2) / LEED Regional Within 500 Miles Of 47150 / EPD and HPD Certified

Warranty

Innovations' wallcoverings are guaranteed to be free of defects in workmanship and material for three years. We cannot accept responsibility for claims if our instructions and terms are not followed, nor are we liable for labor and associated costs, over and above the cost of replacement material.

Care and Maintenance

General maintenance can be achieved with periodic dusting and/or vacuuming of materials using a soft bristle brush. Marks and stains can be cleaned using mild soap and warm water. Avoid all solvent based cleaners and use a blotting technique with a soft sponge. Abrasives and scrubbing can destroy your material face if used. Dry the cleaned area with a lint-free towel.